

Morgan Steel



An extensive range of high quality, low maintenance steel buildings, cabinets and housings in a variety of finishes, sizes and colours designed for modern industrial installations and a multitude of uses.



Morgan Steel

ROADSIDE RANGE AND NON-STANDARD SMALL UNITS

Manufactured from folded steel construction of 2mm mild steel plate to BS EN 10111:1998. Doors are folded steel 2mm mild steel plate and fitted with stainless steel door furniture. Standard locks are Yale or Hasp and Staple or to customers' specification. Units are provided with an all-round internal base flange, 75mm wide, for bolting down.



Double Door Units	Type E	Type F	Type G	Type H	Type J	Type M	Type O
Width							
External	2010	2010	2010	1760	1410	1065	1065
Height							
Maximum	2255	2255	1585	1580	1515	1275	1270
Depth							
External	1750	1250	790	790	660	660	455
Door							
Clear Width	1735	1735	1735	1485	1180	860	860
Clear Height	2000*	2000*	1305	1310	1230	860	86

* denotes removable sill

Single Door Units	Type S	Type R	Type P	Torbay	Torbette	Meter Cabinet	Feeder Pillar
Width							
External	900	900	630	640	640	460	340
Height							
Maximum	1165	1165	1165	1135	910	615	860
Depth							
External	500	330	370	300	300	300	210
Door							
Clear Width	740	755	470	470	470	365	240
Clear Height	700	720	700	700	700	515	710

Standard External Finish

1st coat - Surface tolerant two pack epoxy primer 150 microns DFT.
2nd coat - Polyurethane two pack satin finish to 50 micron DFT.
Available in any colour from the BS4800 range, Green 14-C-39 and Grey 10-A-07 are standard.
Powder coating available as an optional extra.

The above units are also available in :- Hot dipped galvanised to BS EN ISO 1461:1999.
Galvanised steel sheet, treated and painted.
Stainless Steel.

Standard Internal Finish

White Polyurethane Gloss

STEEL MULTIFORM



Housings are constructed from shot blasted and primed Rolled Hollow Section (RHS) frame and clad with 2mm Galv. steel sheet. Welding to BS EN 287 & 288. Insulated units have a standard U value of 0.6. This is achieved by using 50mm Rockwool secured by internal cladding of either sheet steel or treated ply.

Better U values are available on request.

Fire ratings of up to 4 hours are available on request.

All Housings can be supplied with a full range of services and accessories including Mounting Boards, Ventilators, Cat Flaps, Electrics and Air Conditioning.
Full Design, Support and Installation Service.

Morgan Marine Ltd.

Sales, Engineering and Manufacturing

Llandybïe, Ammanford, Carmarthenshire SA18 3JG

Tel: 44 (0)1269 850437 Fax: 44 (0)1269 850656

E-mail: sales@morgan-marine.com

Website: www.morgan-marine.com



BUDDSODDWR MEWN POBL
INVESTOR IN PEOPLE

